

FIRST STEPS

TONE

1

Remove the grey cover from the housing.



2

Connect the blue water hose (Ø8mm) with the TONE 04 and your water supply



Note:
- The TONE 04 needs to be run with filtered water

- The water pressure should be between 3 and maximum 4 bar. A pressure reducer incl. a check valve is supplied with the machine (see picture below) to ensure that no more than 0.4 MPa of water pressure enters the machine and no backflow happens into the drink water network. Install this item into the blue water hose (check the flow direction).



- The delivered connection adapter from TONE has a 3/8-inch thread



3

Plug the machine into the socket. Check out the connection possibilities:

The power supply must relate to one of the following variants:

- 16A three-phase via a CE plug. - Only two phases are used
- 30A single-phase with distribution box from TONE
- 30A three-phase with distribution box from TONE All phases must be shifted by 120°



4

Download the TONE Beverage Manager from the store (Apple, Microsoft, Android) onto your device.

GET THE APP

Please download the software here



5

Build up a connection with a Laptop or tablet to your TONE 04


- Connection by ethernet cable to your laptop or
- Connection by ethernet cable to a Lan switch or
- Connection over Wi-Fi with the IO-GEAR device

6

Follow the instructions on page No. 13 in the manual / or the specific documents


TONE-Setup-IO-Gear.pdf

Rinse the machine by pushing the buttons 1&2 and the main switch (The two buttons will shine up blue and cold water will rinse through the machine until you switch off the machine) This will help to get rid of the air inside of the brewer system.



7

Calibrate the flow of the machine to its new home. Follow the instruction on page No. 17 in the T04 manual.

8

Screw on the basket holder together with the shower



9

Slide in the basket carrier incl. a basket (type 2 or 3)

